

	#100 SERIES PHL MORTAR BINDER	#200 SERIES PHLc MORTAR BINDER	#300 SERIES PHLc FINE POINTING MORTAR	#400 SERIES PHLc70 CRACK FILLER	#500 SERIES PHLc GRAVITY FEED GROUT	#600 SERIES PHLc70 INJECTION GROUT
REBUILDING UNIT MASONRY REPOINTING						
<ul style="list-style-type: none"> UNIT MASONRY RECONSTRUCTION 		For most structures with hydraulic lime and low cement/ high lime mortar blends.	For structures with less than 8 mm (5/16") mortar joint width.			
<ul style="list-style-type: none"> CUTTING AND POINTING 	For pointing over lime-based bedding mortars, and for use with low strength masonry units and adobe.	For pointing over hydraulic lime and cement-lime bedding mortars, with moderate to high strength masonry units.	For pointing of joints less than 8 mm (5/16") wide (butter joints).			
<ul style="list-style-type: none"> FILLING OF COLLAR JOINTS; BONDING BETWEEN RECONSTRUCTED WYTHES 					For filling gaps of 10 mm (3/8") or greater. May be blended with peastone for gaps of 75 mm (3") or greater.	For filling gaps of 3 mm (1/8") to 25 mm (1").
CRACK REPAIR AND RE-BONDING SEPARATED MASONRY						
<ul style="list-style-type: none"> SURFACE FILLING OF CRACKS AND CRAZING 			For filling gaps between 3 mm (1/8") and 8 mm (5/16") wide.	For filling gaps up to 6 mm (1/4") wide.		
<ul style="list-style-type: none"> PRESSURE INJECTING CRACKS AND CAVITIES 						For use with grouting ports and VoidSpan Port Anchors
<ul style="list-style-type: none"> GRAVITY FEED GROUTING OF CRACKS AND CAVITIES 					For filling gaps of 10 mm (3/8") or greater. May be blended with peastone for gaps of 75 mm (3") or greater.	For filling gaps of 3 mm (1/8") to 25 mm (1"). Gaps down to 1 mm (3/64") require special procedures.
<ul style="list-style-type: none"> ADHERING LOOSE FRAGMENTS; BONDING FITTED DUTCHMEN 					For bond line widths down to 2 mm (3/32") when mixed to a paste.	For bond line widths down to 1 mm (3/64") when mixed to a paste.